

All stainless steel gas actuated thermometer

Model GTS

Nominal size 100 mm, 115mm or 150 mm
Accuracy: Class 1 (1%)

Features

- Rugged stainless steel construction
- Fast response
- Protection IP65, IP66, IP67 and IP68
- High repeatability and small hysteresis
- Dry or liquid filled
- Rigid stem or bulb with capillary

Ranges

-200 ... 50 °C up to 0 ... 800 °C
-330 ... 120 °F up to 30 ... 1450 °F


Applications

Chemical and petrochemical industry
Machine and apparatus construction
Food and beverage industry
Pulp and paper industry



Technical specification	Rigid stem			With capillary																				
	100	115	150	100	115	150																		
Dial size in mm	100	115	150	100	115	150																		
Construction	Cylindrical case with bayonet ring																							
Measuring principle	Inert gas actuated																							
Range in °C	0/60 0/80 0/100 0/120 0/160 0/200 0/250 0/300 0/400 0/500 0/600 0/700 0/800 -10/50 -10/110 -20/40 -20/100 -20/120 -20/180 -30/50 -30/70 -30/170 -40/40 -40/60 -40/160 -50/50 -40/60 -40/160 -50/50 -60/40 -80/40 -100/50 -120/40 -200/50																							
Over temperature limit	Ranges in °F and dual scales on request Max. 130 % F.S. Subjected to Max. 825°C Over temperature																							
Stem or bulb diameter	6 mm, 8 mm, 10 mm, 12mm, others on request																							
Lengths	100 ... 4000 mm, other length on request, min. length depends on bulb diameter																							
Capillary length	N.A.			Max. 40 m																				
Process connection	Plain 1/4" 3/4" 1" BSP / NPT (M), M20x1.5, M24x1.5, M27x2 Fixed, adjustable or with swivel nut																							
Connection location	Back / lower / Every angle																							
Material	<table border="0"> <tr> <td>Connection</td> <td>Stainless steel 316L</td> </tr> <tr> <td>Stem</td> <td>Stainless steel 316L (SS 321 for range ≥ 600C)</td> </tr> <tr> <td>Case/ring</td> <td>Stainless steel 304 , optional 316L</td> </tr> <tr> <td>Capillary</td> <td>Stainless steel 316L</td> </tr> <tr> <td>Armor</td> <td>Flexible, SS 304, optional PVC covered</td> </tr> <tr> <td>Window</td> <td>Instrument glass, optional laminated safety glass</td> </tr> <tr> <td>Dial</td> <td>Aluminum, black markings on white background</td> </tr> <tr> <td>Pointer</td> <td>Aluminum, black, optional micrometer pointer others on request</td> </tr> <tr> <td>Movement</td> <td>Stainless steel 304</td> </tr> </table>						Connection	Stainless steel 316L	Stem	Stainless steel 316L (SS 321 for range ≥ 600C)	Case/ring	Stainless steel 304 , optional 316L	Capillary	Stainless steel 316L	Armor	Flexible, SS 304, optional PVC covered	Window	Instrument glass, optional laminated safety glass	Dial	Aluminum, black markings on white background	Pointer	Aluminum, black, optional micrometer pointer others on request	Movement	Stainless steel 304
Connection	Stainless steel 316L																							
Stem	Stainless steel 316L (SS 321 for range ≥ 600C)																							
Case/ring	Stainless steel 304 , optional 316L																							
Capillary	Stainless steel 316L																							
Armor	Flexible, SS 304, optional PVC covered																							
Window	Instrument glass, optional laminated safety glass																							
Dial	Aluminum, black markings on white background																							
Pointer	Aluminum, black, optional micrometer pointer others on request																							
Movement	Stainless steel 304																							
Accuracy	Class 1 as per EN 13190																							
Protection	IP65 / IP66 / IP67 / IP68																							
Filling liquids	Silicone																							
Weight dry/filled in kg	Depend on dial size length of stem and capillary																							
Accessories, options	Thermowells, dual scales, magnet spring- or inductive contacts, calibration certification																							

General dimensions in mm



Order information

Size	Bulb diameter	Length of bulb/stem	Length of capillary	Connection type	Process Connection	Connection orientation	Range	Engineering units	Options	
(100) 100 mm	(06) 6 mm ¹⁾	115 to 4000 mm ²⁾	(R) Rigid stem	(T) Turning nut	(50) 1/2" BSP	(L) Lower	0/ 60	°C	(NH) SS wired tag	
(115) 115 mm	(08) 8 mm ¹⁾			(A) Capillary SS armored*	(CS2) Adjustable union connection sliding on capillary	(75) 3/4" BSP	(B) Back		0/ 80 0/100 0/120 0/160 0/200 0/250 0/300 0/400 0/500	(SD) Special Dial (CS) Dual scale (SG) Safety glass (MP) Micro pointer (FX) Front panel
(150) 150 mm	(10) 10 mm			(P) Capillary SS armored with PVC covering*	(CS3) Adjustable union connection sliding on stem	(50N) 1/2" NPT	(E) Every angle ⁴⁾		0/600 ⁵⁾ 0/700 ⁵⁾ 0/800 ⁵⁾	(FW) Surface plate (UF) U-clamp (TM) 2" pipe mounting bracket
	(12) 12 mm			(SB) Surface Bulb ³⁾	(75N) 3/4" NPT (10N) 1" NPT (M20) M20x1.5 (M32) M32x2 (=) Plain		-10/ 50 -10/110 -20/ 40 -20/100 -20/120 -20/180 -30/ 50 -30/ 70 -30/170 -40/ 40 -40/ 60 -40/160 -50/ 50 -60/ 40 -80/ 40 -100/ 50 -120/ 40 -200/ 50	(EC) Contact type and function (see EC.1) (GR) Glycerin (GV) Silicone (YW) SS316L Case (EZ) External zero adjustment		
			* Max length 40m, specify length in m EG. A1.5 =A with 1.5m	others on request	others on request			°F and dual scale on request	(CD3) 3.1 Material Certi.	
									other options on request	

1) Range up to 500 °C only 2) Minimum stem length depends on stem diameter refer above table 3) For Connection (=) Plain only 4) for rigid stem type only.
5) Stem material will be SS321. Only with bulb diameter 10 mm and 12mm. For rigid stem type minimum length 250mm.

How to order

Size	Type	Bulb diameter	Length of bulb/stem	Length of capillary	Connection type	Process Connection	Connection orientation	Range	Engineering unit	Options	Certificate
100	GTS	08	125	R	CS3	50N	L	0/100	°C	FW	CD3

Precision Mass Products Pvt. Ltd.

Plot No.: 2306, G.I.D.C. Chhatral, Ta: Kalol, Dist.: Gandhinagar, Chhatral -382729, Gujarat, India.

Telephone: +91-2764 233681/82/83

Email: sales@precisionmass.com

Fax: +91-2764-233440

www.precisionmass.com

- North Zone : sales.delhi@precisionmass.com
- East zone : sales.kolkata@precisionmass.com
- West zone : sales.mumbai@precisionmass.com
- South zone : sales.chennai@precisionmass.com